



PROFESSIONALS AT WORK

CRI-MAN®



www.cri-man.com

TBX/E SERIES

• Stainless steel submersible mixers

Technical specifications:

- Made entirely in AISI 316 stainless steel
- Blades in stainless steel with self-cleaning profile
- Rpm: 950 - 1430 (50Hz) 1152 - 1716 (60Hz)
- Motor power: 0,75 - 4 kW
- Axial thrust: 137 - 794 N
- Capacity: 251 - 1448 m³/h
- Max working temp: 40°C



TBM SERIES

• Submersible mixers

Technical specifications:

- Planetary gearbox
- Blades in stainless steel with self-cleaning profile
- Rpm: 275 - 925 (50Hz) 380 - 1130 (60Hz)
- Motor power: 1,5 - 25 kW
- Axial thrust: 230 - 5396 N
- Capacity: 643 - 10138 m³/h
- Max working temp: 40 °C
- ATEX version available



LIABILITY... THROUGH TIME

TMS SERIES

• Mid size submersible mixers

Technical specifications:

- Planetary gearbox
- Blades in stainless steel with self-cleaning profile
- Rpm: 120 (50Hz) 144 (60Hz)
- Motor power: 7.5 - 15 kW
- Axial thrust: 3160 - 4610 N
- Capacity: 8825 - 12210 m³/h
- Max working temp: 40 °C



AF SERIES

• Submersible flow accelerators

Technical specifications:

- Two-stage planetary gearbox
- Adjustable blades
- Blades in polyamide and fiberglass
- Blades hub in stainless steel
- Rpm: 34 (50 Hz) 40 (60 Hz)
- Motor power: 1,5 - 5,5 kW
- Axial thrust: 1226 - 2943 N
- Capacity: 11490 - 17803 m³/h
- Max working temp: 40 °C



PROFESSIONALS AT WORK

PTS SERIES

• Submersible chopper pumps

Technical specifications:

- Double chopping system
- Max capacity: 720 m³/h
- Max Head: 51 m
- Motor power: 0,75 - 45 kW (50 Hz)
- Suction: 65 - 250 mm
- Discharge: 40 - 200 mm
- ATEX version available



ETO ETV SERIES

• Horizontal/vertical chopper pumps

Technical specifications:

- Double chopping system
- Max capacity: 720 m³/h
- Head: 112 m
- Motor power: 0,75 - 75 kW
- Suction: 65 - 250 mm
- Discharge: 40- 200 mm



SM SERIES

• Screw press separators

Technical specifications:

- Screw in AISI 304 treated stainless steel
- Standard Screen in AISI 316 stainless steel
- Planetary gear box
- Sealing system with three lip seals
- Capacity: 4,5 - 72 m³/h
- Motor power: 3 - 11 kW
- Screen mesh: 0,25 - 1 mm
- Up to 38% Dry Matter



PROFESSIONALS AT WORK

CRI-MAN



CRI-MAN SpA - Via del Lavoro, 9/A
42015 CORREGGIO (RE) Italy
Tel. +39 0522 732204 - Fax +39 0522 746363
email: info@cri-man.com - www.cri-man.com



www.cri-man.com

MADE IN
ITALY