



CARATTERISTICHE MOTORI TRIFASE - 50Hz - ALIMENTAZIONE 400 V $\pm 10\%$
50 Hz - THREE-PHASE- MOTOR FEATURES - VOLTAGE RATING 400 V $\pm 10\%$
CARACTERISTIQUES DES MOTEURS TRIPHASES - 50Hz - ALIMENTATION 400 V $\pm 10\%$

CENTRALINA IDRAULICA
HYDRAULIC CONTROL
COMMANDE HYDRAULIQUE

CARATTERISTICHE DEL TRITURATORE
MACERATOR PERFORMANCES
CARACTERISTIQUE DU MACERATEUR

Peso
Weight
Poids

Tipo Type Type	Potenza Motore Motor Rating Puissance Moteur	Avvolgimenti Windings Bobinage	Assorbimento Absorption Intensité	Avviamento Starting Demarrage		Giri/min RPM T/min	Potenza Motore Motor Rating Puissance Moteur	Portata Pompa Pump Capacity Débit de la pompe	Bocca di scanco Outlet Décharge	Produzione max Max production Production max.	Giri/min RPM T/min	[t]
	[kW]	[V]	[A (400V)]	Diretto Direct Direct	Δ Δ		[kW]	[l/min]	[mm]	[t/h]		
BMC-E 55N	55	690-400	95,1	Δ	Δ Δ	2966	2,2	25	440 x 440	10	2400	2,45

DIMENSIONI INGOMBRO [mm] - OVERALL DIMENSIONS [mm] - DIMENSIONS [mm]

